

Electric Duplex



3112DL

Model	Part #	HP	Voltage/ Phase	Tank (Gal)	ACFM @ 100 psi	ACFM @ 175 psi	Max Pressure	Dim. In. L X W x H	Shipping Weight
3112D	8090250005	2x5	208-230/1	120H	37.00	33.20	175 psi	77 x 27 x 56	457 lbs
3312D	8090250018	2x5	208-230/3	120H	37.00	33.20	175 psi	77 x 27 x 56	471 lbs
3312D4	8090250019	2x5	460/3	120H	37.00	33.20	175 psi	77 x 27 x 56	453 lbs
3112DL	8090250006	2x7.5	208-230/1	120H	50.50	44.56	175 psi	77 x 27 x 56	453 lbs
3312DL	8090250020	2x7.5	208-230/3	120H	50.50	44.56	175 psi	77 x 27 x 56	481 lbs
3312DL4	8090250021	2x7.5	460/3	120H	50.50	44.56	175 psi	77 x 27 x 56	481 lbs
3120DL	8090250104	2x7.5	208-230/1	200H	50.50	44.56	175 psi	86 x 32 x 62	467 lbs
3320DL	8090250062	2x7.5	208-230/3	200H	50.50	44.56	175 psi	86 x 32 x 62	467 lbs
3320DL4	8090250112	2x7.5	460/3	200H	50.50	44.56	175 psi	86 x 32 x 62	481 lbs
5312D	8090250044	2x10	208-230/3	120H	74.46	70.74	175 psi	77 x 27 x 63	481 lbs
5312D4	8090250045	2x10	460/3	120H	74.46	70.74	175 psi	77 x 27 x 63	477 lbs
5320D	8090250050	2x10	208-230/3	200H	74.46	70.74	175 psi	86 x 32 x 69	477 lbs
5320D4	8090250051	2x10	460/3	200H	74.46	70.74	175 psi	86 x 32 x 69	481 lbs

Standard Features

- Solid Cast Iron Cylinder
- Dual Pressure Switch Control
- Tri-Voltage Motors (3 Phase)
- Magnetic Starters
- Alternator
- 100% Factory Tested at Full Pressure
- ASME Tank and Safety Valves
- 2 Year Bumper to Bumper Warranty