Propane Forced Air

Our hand carry propane forced air heaters feature enclosed gas controls and heavy-duty steel construction. Ready to use - just connect to propane cylinder and plug-in.















To see more online, scan here



Frame

✓ Heavy-duty steel construction with steel base

Components

- ✓ High performance fan
- ✓ Automatic shut-off if power is interrupted or flame is extinguished
- ✓ Enclosed gas controls
- ✓ Electronic ignition
- ✓ One-touch ignition and heat control for easy operation

For use in workshops, warehouses, garages, construction sites and farms with proper ventilation.

MODEL NUMBER	MH-0060-LM10	MH-0150-LM10	MH-0150-LMT0	MH-0150-NM10	MH-0375-LM10
HEAT OUTPUT	40-50-60,000 BTU	120-135-150,000 BTU	150,000 BTU	150,000 BTU	225-375,000 BTU
HOT-AIR FLOW	300 CFM	400 CFM	400 CFM	435 CFM	1,500 CFM
AC POWER	120V, 60Hz, Less than 1.0 Amps	120V, 60Hz, 1.45 Amps			
MOTOR SIZE	1/10 HP	1/9 HP	1/9 HP	1/9 HP	1/5 HP
FUEL	Propane	Propane	Propane	Natural Gas	Propane
FUEL CONSUMPTION	1.9/2.3/2.8 lb./hr.	5.5/6.2/6.9 lb./hr.	6.9 lb./hr.	146 cu. ft./hr.	10.4 to 17.4 lb./hr.
REQUIRED CYLINDER SIZE	20 lb.	100 lb.	100 lb.	N/A	(2) 100 lb.
MAX. OPERATING HOURS (PER REQUIRED CYLINDER SIZE)	10.5 hours	18.0 hours	18.0 hours	N/A	11.5 hours
HEATING AREA	1,500 sq. ft.	3,800 sq. ft.	3,800 sq. ft.	3,800 sq. ft.	9,000 sq. ft.
ADJUSTABLE THERMOSTAT	No	No	Yes	Yes	Yes
ADJUSTABLE HEIGHT ANGLE	Yes	Yes	Yes	Yes	No
10-F00T HOSE & REGULATOR	Yes	Yes	Yes	No	Yes
DIMENSIONS (LxWxH)	18.1x7.1x13.0in.	25.1x8.7x15.4in.	25.1x8.7x15.4in.	25.1x9x15.5in.	34x12.6x18.5in.
SHIP WT.	19 lb.	29 lb.	29 lb.	35 lb.	49 lb.
NET WT.	15 lb.	23 lb.	23 lb.	24 lb.	41 lb.

Specifications subject to change without notice. Use in accordance with any and all state or local codes, regulations and/or ordinances.

Please see heater "Owner's Manual" included with each heater for a complete list of important safety information. These specifications are estimates only.

ACCC3301 y.					
PART NUMBER	DESCRIPTION	FITS MODELS			
68-5010	Two cylinder manifold	All models			