# **Single-Axle Trailers**

Mi-T-M offers several options for trailer mounted pressure washers. Trailer units are fully integrated and self-contained systems that are designed with a large water supply tank for working at remote sites where water is not accessible. The heavy-duty construction of the trailer and the axle suspension provide an easy ride to ensure the longevity of your equipment. Add a high quality Mi-T-M pressure washer and you have the power required to get large jobs done quickly, wherever you need to work.



MODEL NUMBER	WATER TANK	BRAKES	COUPLER	TIRES	AXLES	TRAILER DECK PLATE	ANGLE FRAME	TRAILER BED DIM.	GROSS VEHICLE WT.
AW-9000-0005	200-gallon	Surge	2in.	(2) ST205-75R 15in. radial	(1) 3,500 lb.	.25in. solid steel	3in.x4.25in.	5ft.x8.5ft.	3,500 lb.
AW-9000-0006	200-gallon	Electric	2in.	(2) ST205-75R 15in. radial	(1) 3,500 lb.	.25in. solid steel	3in.x4.25in.	5ft.x8.5ft.	3,500 lb.
AW-9000-0007	200-gallon	None	2in.	(2) ST205-75R 15in. radial	(1) 3,500 lb.	.25in. solid steel	3in.x4.25in.	5ft.x8.5ft.	3,500 lb.

#### **Trailer Options for Single & Dual-Axle Trailers**

#### **High Pressure Hose Reel Options**

These high pressure hose reel options include a hose reel with jumper hose and mounting bracket.

**TX-0001** (13-inch reel)

**TX-0002** (16-inch reel)

### **Low Pressure Hose Reel Options**

These low pressure hose reel options include a hose reel with mounting bracket and plumbing.

**TX-0003** (16-inch reel)

Note: 22-0136 back-flow preventor must be used with TX-0003, when used in California.

#### **Back-Flow Preventor**

These back-flow preventors are required on trailer units in some states.

**22-0136** (Use if a trailer has a hose reel for the supply)

- ✓ Mounted on inlet side of trailer
- ✓ To be used with TX-0003 low pressure hose reel option

# **Trailer Tank Bypass**

TX-0005 (Dual-axle trailer tank bypass - for use with HS Series)

**TX-0007** (Single-axle trailer tank bypass - for use with HS Series)

✓ Removes the float system, while adding the necessary plumbing

✓ Water bypasses back to water tank

# **Replacement Hose Reel Parts**

When adding hose reels to the single or dual-axle trailers, use the following jumper hose and mounting bracket.

**15-0159** (Jumper hose)

**13-0179A01** (Mounting bracket)

**50-0195** (13-inch reel, 150-foot maximum hose length)

50-0196 (16-inch reel, 200-foot maximum hose length)