## SUPERMAX DOUBLE DRUM SANDERS 25"/ 37"/50" WIDTHS



## **EXCEPTIONAL SUPERMAX FEATURES**

- SandSmart Control: Automatically adjusts conveyor speed based on load
  - Prevents gouging, damaging or burning stock
  - Provides consistent finish even with varying grain pattern and density
  - Greatly increases abrasive planing and dimensioning speed
- Flatness Guarantee: Precision-flattened steel conveyor bed reinforced with four steel cross sections for no "flex" in conveyor, guaranteeing flatness to less than .010" across the width of the sander
- Abrasive conveyor belt offers the best grip for raw wood, giving you the ability to accommodate stock that is much shorter or thinner
- Patented Abrasive Attachment System effectively tensions the abrasive wraps, preventing loose abrasive and overlap
- Self-cooling drum prevents overheating and extends abrasive life

Sanding Capacity:	· ·
Maximum Width (in):	25, 37 or 50
Minimum Length (in):	3-1/2
Maximum Thickness (in):	25" model: 6 37" & 50" models: 12
Minimum Thickness (in):	1/32
Dimensions H x W x D (in):	25" model: 43 x 46 x 31 37" model: 43 x 58 x 31 50" model: 50 x 71 x 31
Drum (in): extruded aluminum	25" model: 5 x 25 37" model: 5 x 37 50" model: 5 x 50
Drum speed:	1740 RPM
Dust Hood: steel, hinged at back	25" model: (2) - 4" ports, min. 1000 CFM recommended 37" & 50" models: (3) - 4" ports, min. 1800 CFM recommended
Ball Bearings (1"):	4 - permanently sealed and lubricated
Conveyor Motor :	25" & 37" models: 100 inlb. torque, direct drive D.C motor, infinitely variable, 0-15 FPM 50" model: 220 inlb. torque, direct drive D.C motor, infinitely variable, 0-15 FPM
Drive Motor (TEFC):	25" & 37" models: 5 HP 50" model: 7-1/2 HP
Power Requirements:	208-230V, 60HZ; 1 PH, 30 amp service; 3 PH, 20 amp service
Shipping Weight (lbs):	25" model: 475 37" model: 525 50" model: 820



## ADDITIONAL FEATURES

- Cast stand, zinc-plate steel bed, centerless ground column tubes
- Drums are wrapped with 80 and 120 grit sandpaper
- Swivel & lock casters included on 37" and 50" models
- Electric Height Adjustment and Digital Read Out included on 50" model

Item#	Description
913002	25x2 Double Drum Sander- 220V, 5 HP, Single Phase
913102	25x2 Double Drum Sander- 220V, 5 HP, 3 Phase
937003	37x2 Double Drum Sander- 220V, 5 HP, Single Phase
937103	37x2 Double Drum Sander- 220V, 5 HP, 3 Phase
750102	50x2 Double Drum Sander- 220V, 7-1/2 HP, Single Phase
750302	50x2 Double Drum Sander- 220V, 7-1/2 HP, 3 Phase

25" and 37" models are made in Taiwan to SuperMax specifications. The 50" model is made in the USA.