



20TH ANNIVERSARY SPECIAL

680GC CONCRETE CHAIN SAW

ONLY \$995 - ACT NOW!

INCLUDES FREE 12-INCH DIAMOND CHAIN & GUIDE BAR

- Available Feb 1, 2010 - Sept 30, 2010
- Available in North America Only
- Other terms and conditions apply
- See your ICS participating Dealer for details



Applications

- Foundation Vents
- Egress Windows
- Concrete Pipe
- HVAC Duct Openings
- Beam Pockets
- Hardscaping

Materials

- Concrete
- Masonry
- Brick
- Block
- Stone

For more information or to order, please contact:

680GC PRODUCT SPECIFICATIONS

WEIGHT	21 lbs (9.5 kg) with bar and chain
BAR LENGTH	Up to 14 in (35 cm)
ENGINE SPEED	11500 +/- 500 rpm, 2800-3200 rpm idle
HORSEPOWER	5.7 hp (4.2 kW) @ 9000 rpm
ENGINE TYPE	2-stroke, single cylinder, air cooled
DISPLACEMENT	4.9 cu inch (80 cc)
POWERHEAD DIMENSIONS	18 in (45 cm) length 11.5 in (29 cm) height 10 in (25 cm) width
NOISE LEVEL	100 dB @ 3 ft (1 m)
VIBRATION LEVEL	10.5 meters/second ² (front handle)
WATER SUPPLY	Minimum 20 psi (1.5 bar)
FUEL MIX RATIO	25:1 (4%) fuel-to-oil
FUEL CAPACITY	0.23 gal (.88 liter), 15-18 minutes run time per tank