

# 100 TON DELUXE



Five Loaded Workstations
Built-in Rod Shear for Square
and Round Bar
18" Flat Bar Shear

Dedicated Coper Notcher Electric Stroke Control ANSI B11.5-1988R(02) Compliant ETL/UL Approved Controls

A brute of an Ironworker, the Edwards 100 Ton Deluxe JAWS Ironworker features super-duty construction and a powerful 10hp motor. Standard features include a Punch Assembly, 18" wide Flat Bar Shear, Angle Shear, Coper Notcher and a special built-in Rod Shear for solid square and round bar stock.

# **PUNCH**

Rating: 100 Tons
Max. Capacity: 1-1/16" Dia. in 1" A36
Stroke: 1-15/16"
Throat Depth: 11"
Open Height: 8-3/4"

Shut Height: 6-13/16" Work Height: 39-3/8"

# **ANGLE SHEAR**

Max. Capacity: 6" x 6" x 1/2" Work Height: 43-15/16"

# **FLAT BAR SHEAR**

Max. Capacity: 1/2" x 18" 3/4" x 14"

1" x 10"

Max. Round: 1"
Max. Square: 1"
Work Height: 37"

# **COPER NOTCHER**

Max. Capacity: 2-1/2" x 6" x 1/2"

Work Height: 42"

### **ROD SHEAR**

Max. Round: 1-1/2" Max. Square: 1-1/4" Work Height: 54-1/2"

# **GENERAL SPECIFICATIONS**

Standard Motor: 10 HP 3~ 208 V or 230 V

1770 RPM 26 A

Optional Motors: 10 HP 3~ 460 V

1770 RPM 12 A 10 HP 3~ 575 V 1770 RPM 10 A 10 HP 1~ 230 V

10 HP 1~ 230 V 1740 RPM 40 A

Hydraulic Pump: 24 GPM
Valve Pressure: 3800 PSI
Reservoir: 17 Gallons
Cylinder: 2-1/2" Ram

### **DIMENSIONS**

 Height:
 63-1/8"

 Width:
 56"

 Depth:
 45-1/2"

 Shipping Weight:
 5180 lb

CALL (800) 373-8206