120 TON

The Powerhouse

Five Available Workstations Universal Open Tooling Station 24" Flat Bar Shear **Dedicated Coper Notcher**

Electric Stroke Control ANSI B11.5-1988R(02) Compliant **ETL/UL Approved Controls**

Our most powerful Ironworker, the Edwards 120 Ton JAWS Ironworker offers the most in capacity and versatility. Standard features include a Punch Assembly, 24" wide Flat Bar Shear, high capacity Angle Shear, Coper Notcher and a universal open tooling station for optional Tooling Accessories allowing you to select the perfect tool for your needs.

PUNCH

Rating: 120 Tons

Max. Capacity: 1-1/2" Dia. in 1" A36

Stroke: 2-1/2" Throat Depth: 11" Open Height: 9-1/8" Shut Height: 7" Work Height: 36-5/8"

ANGLE SHEAR

Max. Capacity: 6" x 6" x 1/2" Work Height: 52-1/2"

FLAT BAR SHEAR

Max. Capacity: 1/2" x 24"

1" x 12"

Max. Round: 1-1/4" Max. Square: 1-1/4" Work Height: 33-1/4"

COPER NOTCHER

Max. Capacity: 2-1/2" x 6" x 1/2" Work Height: 40"

OPEN CAVITY

Height: Width: 11-3/4" Work Height: 51-3/4"

GENERAL SPECIFICATIONS

Standard Motor: 10 HP 3~ 208 V or 230 V

1770 RPM 26 A

Optional Motors: 10 HP 3~ 460 V

1770 RPM 12 A 10 HP 3~ 575 V 1770 RPM 10 A

10 HP 1~ 230 V 1740 RPM 40 A

Hydraulic Pump: **24 GPM** Valve Pressure: 3800 PSI 17 Gallons Reservoir:

2-3/4" Ram Cylinder:

DIMENSIONS

Height: 84" Width: 60" Depth: 60" **Shipping Weight:** 5500 lb

