



60 TON

Our Best Value

- Four Loaded Workstations
- Dedicated Coper Notcher Station
- Electric Stroke Control
- ANSI B11.5-1988R(02) Compliant
- ETL/UL Approved Controls

The Edwards 60 Ton JAWS Ironworker is a robust machine featuring a dedicated Coper Notcher station, adding strength and stability to this great tool. Standard features include a Punch Assembly with Pedestal Die Table, 14" wide Flat Bar Shear, Angle Shear and Coper Notcher.

PUNCH

Rating: 60 Tons
 Max. Capacity: 1" Dia. in 3/4" A36
 Stroke: 1-1/4"
 Throat Depth: 8-7/8"
 Open Height: 8-1/8"
 Shut Height: 6-7/8"
 Work Height: 36-9/16"

ANGLE SHEAR

Max. Capacity: 3" x 3" x 1/2"
 4" x 4" x 3/8"
 Work Height: 39-7/8"

FLAT BAR SHEAR

Max. Capacity: 3/8" x 14"
 1/2" x 12"
 3/4" x 4"

Max. Round: 7/8"
 Max. Square: 7/8"
 Work Height: 34-1/2"

COPER NOTCHER

Max. Capacity: 2-1/2" x 4" x 3/8"
 Work Height: 39-1/2"

GENERAL SPECIFICATIONS

Standard Motor: 5 HP 3~ 208 V or 230 V
 1725 RPM 14 A
 Optional Motors: 5 HP 3~ 460 V
 1725 RPM 7 A
 5 HP 3~ 575 V
 1725 RPM 6 A
 5 HP 1~230 V
 1725 RPM 23 A
 Hydraulic Pump: 3-1/2 GPM - 1 Stage
 Valve Pressure: 2500 PSI
 Reservoir: 7 Gallons
 Cylinder: 2-1/2" Ram

DIMENSIONS

Height: 56-1/8"
 Width: 46-1/8"
 Depth: 36-1/8"
 Shipping Weight: 2550 lb



CALL (800) 373-8206

WWW.EDWARDSIRONWORKERS.COM