

**WT3000H** 

POWERED by
HONDA



## **Engine:**

- Honda GX160 OHV
- · CARB & EPA certified
- Cast iron cylinder sleeve
- · Commercial grade OHV engine
- 3 year commercial warranty is included standard
- High compression ratio for better fuel efficiency
- Ball bearing supported crankshaft for greater stability
- Aluminum push rods reduce both valve clearance and noise level
- Dual element air cleaner
- Automatic mechanical de-compression system

## **Generator End:**

- Wound in the USA
- Brushless design
- Circuit breaker protection
- 100% copper windings longer life and improved motor starting
- 100% load tested (Not statistically sampled)
- Self regulating output voltage

## **Components:**

- 1 gallon steel fuel tank
- Powder coat paint on steel components for an incredibly durable finish
- Sturdy wrap around cradle protects the engine and generator from damage
- USFS approved spark arrestors
- GFCI protected for worksites

SURGE WATTS	3000
CONTINUOUS WATTS	2500
AMPS	20.8
VOLTS	120
VOLTAGE REGULATION	+/-5%
FREQUENCY REGULATION	+/-3%
ENGINE BRAND	HONDA
ENGINE MODEL	GX160 OHV
ENGINE STARTER	RECOIL
ENGINE SPEED	3600 RPM
DISPLACEMENT	160 CC
ENGINE CYLINDERS	SINGLE
LOW OIL PROTECTION	STANDARD
dBA AT 7 METERS	74
FUEL TANK	1 GAL
FULL LOAD RUN TIME	2.2 HOURS
FUEL USE (GAL/HR)	0.45 GAL/HR
MOTOR STARTING (CODE G)	1 HP
MAIN CIRCUIT BREAKER	20 AMPS
HOUR METER	NA
120 VOLT RECEPTACLES	(1) NEMA 5-20R DUPLEX
DIMENSIONS (LxWxH)	24" x 17.5" x 18"
NET WEIGHT	96 LBS
SHIP WEIGHT	102
WARRANTY (ENG/GEN)	3 YRS / 2 YRS

Toll Free: 1-800-733-2112 sales@wincogen.com

www.wincogen.com

Presented by

225 South Cordova Avenue Le Center MN, 56057