

Contractor Series



T1530

Single Stage Electric

Model	Part #	HP	Voltage/ Phase	Tank (Gal)	ACFM @ 40 psi	ACFM @ 100 psi	Max Pressure	Dim. In. L X W x H	Shipping Weight
T1530	8090250700	1.5	115/1	2 x 4	5.89	5.35	130 psi	46 x 23 x 26	130 lbs
T2030	8090250701	2	115/230/1	2 x 4	7.61	6.50	130 psi	46 x 23 x 26	130 lbs

Standard Features

- Solid Cast Iron Cylinder
- Start-Stop Pressure Switch Control

- Fully Enclosed High Flow Belt Guard
- 3/8" Outlet

TH5530



TH908

Single Stage Gas

Model	Part #	HP	Engine	Tank (Gal)	ACFM @ 40 psi	ACFM @ 100 psi	Max Pressure	Dim. In. L X W x H	Shipping Weight
TH5530	8090250705	5.5	Honda	2 x 4	13.58	12.35	130 psi	46 x 23 x 26	221 lbs
TR6030	8090250709	6	Robin	2 x 4	13.58	12.35	130 psi	46 x 23 x 26	221 lbs

Two Stage Gas

Model	Part #	HP	Engine	Tank (Gal)	ACFM @ 100 psi	ACFM @ 175 psi	Max Pressure	Dim. In. L X W x H	Shipping Weight
TR908	8090250710	9	Robin	2 x 5	18.50	16.60	175 psi	50 x 29 x 37	316 lbs
TH908	8090250706	9	Honda	2 x 5	18.50	16.60	175 psi	50 x 29 x 37	316 lbs
TK128-I	8090250708	12.75	Kohler	2 x 5	25.25	22.28	175 psi	50 x 29 x 37	345 lbs

Standard Features

- Solid Cast Iron Cylinder
- Engine Slow Down (Pilot Valve)

- Engine Oil Monitor
- 3/8" Outlet

Gas Drive Contractor Series Compressors equipped with Recoil Start (TK128-I has Electric and Recoil Start)