

PM1200 Air Filtration System



PM1200 Air Filtration System



The PM1200 Air Filtration System traps 99% of all 5-micron particles and 85% of all 1-micron particles for a healthier work environment. Three blower speeds modify air flow. The unit can be operated either at the cabinet or with the remote transmitter which uses radio-frequency, eliminating the need for line-of-sight operation. A programmable timer has nine settings, allowing continuous operation for up to 9 hours while you're away, and will shut off at the end of that period. The filter guards are removed and installed easily without tools for quick access to filters.

FEATURE

Remote control operates on radio frequency for wider range of effectiveness

Three blower speeds to modify air flow

Timer has nine settings, for up to nine hours of continuous operation

Three filter system includes diffuser to disperse exhausted air

Inner filter has fine mesh pockets for high efficiency, can be blown or washed clean

Electrostatic outer filter is disposable

Four eye bolts allow suspension from shop ceiling

Indicator lights up after 200 hours to remind user to replace filters

Filter guards snap on and off easily for quick access to filters

Two carry handles for portability

Fully enclosed motor has overload protection for long service life



Guard slides off without tools, for instant access

Model Number	PM1200
Stock Number	1791330
Efficiency of Outer Filter	99 % of 5 micron particles
Efficiency of Inner Filter	85 % of 1 micron particles
Remote Transmitter	radio frequency
Blower Speeds	3
Timer Settings (hours)	1 to 9
Cabinet Material	20 gauge steel
Overall Dimensions (L x W x H)(in.)	33 x 25 x 13
SOUND RATING @ 3.28 FEET	
High Speed	65 dB
Medium Speed	58 dB
Low Speed	52 dB
AIR FLOW, FILTERED	
High Speed	1196 CFM
Medium Speed	706 CFM
Low Speed	547 CFM
Motor	1/4HP, 1 PH, 115V only
Amps	3.5 / 2.8 / 2.3
Net Weight, approximate (lbs.)	67
Shipping Weight, approximate (lbs.)	74



RF remote control with LCD