



Folding Pipe Jacks

Pipe and Industrial Tools



Specifications

- 2,500 lbs standard V-Head weight capacity rating.
- Two sizes: 32-48" Standard and 22-39" Low profile.
- Third party tested with at least a 2:1 safety ratio.
- Oversized 10 inch V-Head for increased safety.
- 1 ¼ square tube legs for increased durability.
- 1 ½ inch acme rod is the largest in the industry.
- More head options than any manufacturer.
- Increased width in stance for better stability.
- No slip washer can be locked onto the base for safety.
- Unique bottom lock T-Handle reduces fit up wobble.
- Fully welded carry handle doubles as security lock point.



PN	NAME	WEIGHT CAPACITY	DIMENSIONS (L x W x H)	ADJUSTMENT HEIGHT	SHIPPING WEIGHT
3900	V-Head Pipejack	2,500 lbs.	22 x 22 x 30	32-48 inches	26
3904	Hold Down Head	1,000 lbs.	22 x 22 x 32	32-48 inches	36
3905	Roller Head w/Steel Wheels	2,000 lbs.	22 x 22 x 31	32-48 inches	28
3910	Roller Head w/ Rubber Wheels	1,000 lbs.	22 x 22 x 31	32-48 inches	28
3935	Roller Head w/Stainless Wheels	2,000 lbs.	22 x 22 x 31	32-48 inches	28
3915	Conveyor Roller Head	1,000 lbs.	22 x 22 x 29	32-48 inches	32
3920	Conveyor V Roller Head	2,000 lbs.	22 x 22 x 36	32-48 inches	36
4000	V-Head Pipejack	2,500 lbs.	20 x 20 x 25	22-39 inches	23
4005	Roller Head w/Steel Wheels	3,000 lbs.	20 x 20 x 26	22-39 inches	27

BBPipeTools.com

Phone: 713-747-8502

Fax: 713-747-8505

Email: sales@bbpipetools.com