

Air Compressors 30 & 80-Gallon/Base-Mount

Two Stage Gasoline



This two-stage air compressor provides the high capacity air flow required for most commercial, industrial, automotive and service body applications.

To see more online, scan here or go to www.mitm.com:



Compressor Pump

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Engine

- Electric start standard - battery and cables not included

Frame

- Powder coated ASME coded 30 or 80-gallon receiver tank (Tank-mounted models only)
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- Removable base plate offers flexible installation

Components

- Regulator and two gauges for tank and outlet pressure
- ASME safety valves
- 16.5-inch fly wheel
- Tank drain valve
- Service truck mount kit (Standard on base-mount models only)



ABS-14S-80H

Limited Warranties:

2 Year
Pump Exchange

See page 60 for information

3 Year
Kohler Engine



UM
30-Gallon
Models



U
80-Gallon
Models

3 Year
Honda Engine

5 Year
Subaru Engine

TANK-MOUNTED								
MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
ABS-13H-30H	29.0 @ 175	389cc Honda OHV	Two stage, cast iron	30-gallon	Pneumatic	42x19x45in.	480 lb.	416 lb.
ABS-14K-30H	29.0 @ 175	429cc Kohler OHV	Two stage, cast iron	30-gallon	Cable throttle	42x19x45in.	480 lb.	416 lb.
ABS-14S-30H	29.0 @ 175	404cc Subaru OHC	Two stage, cast iron	30-gallon	Cable throttle	42x19x45in.	480 lb.	416 lb.
ABS-13H-80H	29.0 @ 175	389cc Honda OHV	Two stage, cast iron	80-gallon	Pneumatic	52x26.5x53in.	560 lb.	496 lb.
ABS-14S-80H	29.0 @ 175	404cc Subaru OHC	Two stage, cast iron	80-gallon	Cable throttle	52x26.5x53in.	560 lb.	496 lb.

BASE-MOUNTED								
MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
ABS-13H-B	29.0 @ 175	389cc Honda OHV	Two stage, cast iron	Base-mount	Pneumatic	36.5x19x28in.	279 lb.	215 lb.
ABS-14S-B	29.0 @ 175	404cc Subaru OHC	Two stage, cast iron	Base-mount	Cable throttle	36.5x19x28in.	279 lb.	215 lb.

*Equipped with 150-PSI maximum rated regulator.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
3-0304	Pump	All models	IX-0001	Vibration pads; recommended for models that are mounted in service truck applications	30 & 80-gallon models
33-0407	Cable throttle control	ABS-13H-30H & ABS-13H-B	IX-0055	Remote start/choke; 6-ft. wire extension for key switch	Honda models
33-0548	Cable throttle control	ABS-13H-80H			
AW-6000-1002	Equipment cover	30-gallon & base-mount models			