

Single Stage Gasoline

The 20-gallon single stage gasoline air compressor features a rugged handle and large tires to easy maneuver across uneven surfaces.

To see more online, scan here or go to www.mitm.com:



Compressor Pump

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Frame

- Powder coated ASME coded 20-gallon receiver tank
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- Flat-free tires

Components

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 12-inch fly wheel
- Quality pilot valve unloader



AM1-PH65-20M

Limited Warranties:

2 Year Pump Exchange **3 Year** Honda Engine **5 Year** Subaru Engine

See page 60 for information



MODEL NUMBER	CFM @ PSI	DISPLACEMENT/ENGINE	COMPRESSOR	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PH65-20M	13.9 @ 90	196cc Honda OHV	Single stage, cast iron	20-gallon	Pneumatic	37x23.5x33in.	272 lb.	212 lb.
AM1-PR07-20M	13.9 @ 90	211cc Subaru OHC	Single stage, cast iron	20-gallon	Cable throttle	37x23.5x33in.	272 lb.	212 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
33-0294	Cable throttle control	AM1-PH65-20M	AW-6000-1002	Equipment cover	All models
7-0228A01	Rear lifting handle	All models	AX-0003	Manual drain/regulator/metal bowl	All models
70-0357	Engine oil drain extension	AM1-PH65-20M	AX-0027	Stationary kit	All models
70-0380	Engine oil drain extension	AM1-PR07-20M	AX-0067	Electric start - battery and cables not included	AM1-PR07-20M