

# Two Stage Gasoline

Strong and durable, this unit can store ample pressure and is available in both portable or stationary.

## 20-Gallon

Limited Warranties:

**2 Year**  
**Pump Exchange**  
 See page 58 for information



**3 Year**  
**Honda Engine**



AM2-SH09-20M shown with AX-0015 (electric start option)

### Compressor Pump

- ✓ Stainless-steel braided discharge hose
- ✓ Large canister intake filter

### Frame

- ✓ Powder coated ASME coded 20-gallon receiver tank
- ✓ 3/16-inch base plate to reduce vibration
- ✓ 14-gauge powder coated two-piece belt guard

### Components

- ✓ Regulator and two gauges for tank and outlet pressure
- ✓ Manual drain valves for proper maintenance
- ✓ 16.5-inch fly wheel
- ✓ Quality pilot valve unloader

To see more online, scan here or go to [www.mitm.com](http://www.mitm.com):



#### PORTABLE MODEL

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-PH09-20M	17.2 @ 175	270cc Honda OHV	Two stage	Cast iron	Splash lubricated cast iron	20-gallon	Pneumatic	46x26x39.5in.	356 lb.	306 lb.

#### STATIONARY MODEL

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	COMPRESSOR	CYLINDER	CRANKCASE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-SH09-20M	17.2 @ 175	270cc Honda OHV	Two stage	Cast iron	Splash lubricated cast iron	20-gallon	Pneumatic	37x18x38in.	356 lb.	306 lb.

\*Equipped with 150-PSI maximum rated regulator.

#### Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
33-0294	Cable throttle control	All models	AX-0003	Manual drain/regulator/metal bowl	All models
AW-0007-0196	Rear lifting handle (N/A for models with electric start option)	AM2-PH09-20M	AX-0015	Electric start (battery and cables not included)	All models
AW-6000-1002	Equipment cover	All models	AX-0017	Electric start (battery and cables included)	All models