

Cold Water Gasoline Direct Drive

CA Aluminum Series

Fitted with our patented vibration isolation plate, the CA Series aluminum pressure washer is lightweight yet rugged.



Patented vibration isolation plate with four rubber isolators for reduced movement

Pump

- Direct drive triplex piston AR or General pump with ceramic plungers
- General pumps feature an external bypass system which allows more water into the system to protect from heat build-up
- Stainless-steel and brass unloader with adjustable pressure
- Forged brass manifold
- Thermal relief valve
- In-line water strainer

Engine

- Performance-proven engine with low-oil protection

Frame

- Light, corrosion resistant aluminum frame
- 1-inch aluminum tube handles for easier pulling
- Aluminum base plate and solid full-length axle
- Convenient nozzle holder for quick connect nozzles
- Pneumatic tires and dual rubber isolators



CA-2703-0MKB



Units Include:

- Quick connect nozzles (0°, 15° and 25°)
- 50-foot x 3/8-inch non-marking hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip (48-inch lance on 3500 & 4000-PSI models)

Warranties

3 YEAR LIMITED HONDA ENGINE WARRANTY	3 YEAR LIMITED KOHLER ENGINE WARRANTY	5 YEAR LIMITED SUBARU ENGINE WARRANTY	7 YEAR LIMITED PUMP WARRANTY
---	--	--	---

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CA-2403-0MHB	2400	2.4	196cc Honda OHV	AR	39in.x20.5in.x24.5in.	100 lb.	73 lb.
CA-2403-0MRB	2400	2.4	211cc Subaru OHC	AR	39in.x20.5in.x24.5in.	100 lb.	73 lb.
CA-2703-0MHB	2700	2.4	196cc Honda OHV	AR	39in.x20.5in.x24.5in.	100 lb.	73 lb.
CA-2703-0MKB	2700	2.4	208cc Kohler OHV	AR	39in.x20.5in.x24.5in.	100 lb.	73 lb.
CA-2703-0MRB	2700	2.4	211cc Subaru OHC	AR	39in.x20.5in.x24.5in.	100 lb.	73 lb.
CA-3003-0MHB	3000	3.0	270cc Honda OHV	AR	42.5in.x23.5in.x24.5in.	155 lb.	105 lb.
CA-3003-0MKB	3000	3.0	277cc Kohler OHV	AR	42.5in.x23.5in.x24.5in.	155 lb.	105 lb.
CA-3003-0MRB	3000	3.0	265cc Subaru OHC	AR	42.5in.x23.5in.x24.5in.	155 lb.	105 lb.
CA-3504-0MHB	3500	3.5	389cc Honda OHV	AR	42.5in.x23.5in.x24.5in.	175 lb.	125 lb.
CA-3504-0MRB	3500	3.5	404cc Subaru OHC	AR	42.5in.x23.5in.x24.5in.	175 lb.	125 lb.
CA-3504-1MHB*	3500	4.0	389cc Honda OHV	General	42.5in.x23.5in.x24.5in.	175 lb.	125 lb.
CA-4004-0MHB	4000	3.5	389cc Honda OHV	AR	42.5in.x23.5in.x24.5in.	175 lb.	125 lb.
CA-4004-0MKB	4000	3.5	429cc Kohler OHV	AR	42.5in.x23.5in.x24.5in.	175 lb.	125 lb.
CA-4004-0MRB	4000	3.5	404cc Subaru OHC	AR	42.5in.x23.5in.x24.5in.	175 lb.	125 lb.
CA-4004-1MHB*	4000	4.0	389cc Honda OHV	General	42.5in.x23.5in.x24.5in.	175 lb.	125 lb.

*Model comes standard with external bypass system and General pump.

ACCESSORIES & OPTIONS

PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injection - High pressure water mixes with detergent to clean even the heaviest build-up	All models
AW-8400-0021	Low pressure detergent injection - Allows the user to apply the recommended detergents	All models
CX-0005	Insulated dual lance - Has both a high and low pressure tip that allows you to switch to the low pressure chemical injector without having to change tips	All models
CX-0097	External bypass - Allows more water into the system to protect from heat build-up	2400 to 2700-PSI models
CX-0098	External bypass - Allows more water into the system to protect from heat build-up	3500 to 4000-PSI models except 1MHB
CX-0099	External bypass - Allows more water into the system to protect from heat build-up	3000-PSI models