

Dual-Axle Trailers

Mi-T-M offers several options for trailer mounted pressure washers for the ultimate in portable cleaning. Trailer units are fully integrated, self-contained systems and are designed with a large water supply tank for working at remote sites where water is not accessible. The heavy-duty construction of the trailer and the axle suspension provides an easy ride ensuring the longevity of your equipment. Add a high quality Mi-T-M pressure washer and you are ready to deliver big power to get big jobs done quickly, wherever you need to work.

AW-9000-0003 (With surge brakes and (2) 200-gallon water tanks)

AW-9000-0004 (With electric brakes and (2) 200-gallon water tanks)

- 5-foot x 8½-foot trailer
- 3-inch x 4¼-inch angle frame
- 7,000-lb. gross vehicle weight
- (2) 3,500-lb. axles with brakes on both sides
- (4) ST205-75R 15-inch radial tires with 6-bolt white spoke rims
- (2) Tandem fenders
- 2⅝-inch coupler with 14,000-lb. capacity
- Swivel jack with pad
- Rubber mounted sealed lights
- Tanks are enclosed in a powder coated steel frame
- 5-foot x 4-foot x 12-inch storage area located under the water tanks, access doors are located at back of trailer
- Pressure washers sit on solid ¼-inch steel base (will fit all Mi-T-M pressure washers)
- Aluminum treadplate steps for access to water tanks
- (2) 200-gallon tanks are plumbed together

Accessories for Dual-Axle Trailers

- Pressure washers
- Hose reels



Storage area located under the water tanks



Trailer shown with HS-3505-1MGH hot water pressure washer and hose reels (available as accessories)

Dual-Axle Trailers

AW-9000-0008 (With surge brakes and (1) 200-gallon water tank)

- 5-foot x 8½-foot trailer
- 3-inch x 4¼-inch angle frame
- 7,000-lb. gross vehicle weight
- (2) 3,500-lb. axles with brakes on both sides
- (4) ST205-75R 15-inch radial tires with 6-bolt white spoke rims
- (2) Tandem fenders
- 2-inch coupler with 14,000-lb. capacity
- Swivel jack with pad
- Rubber mounted sealed lights
- Tank is enclosed in a powder coated steel frame
- Pressure washers sit on solid ¼-inch steel base (will fit all Mi-T-M pressure washers)
- Aluminum treadplate steps for access to water tank



AW-9000-0008 shown with HS-3006-OMDK hot water pressure washer and hose reel (available as accessories)

Accessories for Dual-Axle Trailers

- Pressure washers
- Hose reels

Trailer Options for Dual-Axle Trailers

High Pressure Hose Reel Options

These high pressure hose reel options include the hose reel with jumper hose and mounting bracket.

TX-0001 (13-inch reel)

TX-0002 (16-inch reel)

Low Pressure Hose Reel Options

These low pressure hose reel options include the hose reel with mounting bracket and plumbing.

TX-0003 (16-inch reel)

Note: 22-0136 back-flow preventor must be used with TX-0003, when used in California.

Replacement Hose Reel Parts

When adding hose reels to the single or dual-axle trailers, use the following jumper hose and mounting bracket.

15-0159 (Jumper hose)

13-0179A01 (Mounting bracket)

50-0136 (13-inch reel, 100-foot maximum hose length)

50-0137 (16-inch reel, 200-foot maximum hose length)

Back-Flow Preventors

These back-flow preventors are required on trailer units in some states.

22-0136 (Use if a trailer has a hose reel for the supply)

- Mounted on inlet side of trailer
 - To be used with TX-0003 Low pressure hose reel option
- TX-0005** (Trailer tank bypass - for use on HS Series models)
- Removes the float system, while adding the necessary plumbing
 - Water bypasses back to water tank

Due to advancements in technology, the design of Mi-T-M trailers may change after the publication of this catalog.