# 13000 & 14000-Watt

Portable Generators

## Gasoline

This portable generator is built to withstand the most demanding work conditions and can easily be transported from jobsite to jobsite.

*To see more online, scan here or go to www.mitm.com:*

**Alternator**
- *Total harmonic distortion (THD) less than 5%*
- *100% copper windings*

**Frame**
- *Reinforced 1¼-inch powder coated steel tube frame*
- *Pneumatic tires*

**Components**
- *Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles*
- *Large low-tone mufflers*
- *Easy-to-read fuel gauge*
- *Voltmeter/hour meter*
- *Heavy-duty industrial air cleaner*

**Miscellaneous**
- *USDA/USFS-approved spark arrestors*

*GEN-14000-1MHE*

*Limited Warranties:*

**2 Year** Alternator

**5 Year** Subaru Engine

**3 Year** Honda Engine

CSA CERTIFIED

GFCI 5-20R | NEMA L14-30R 120V/240V | NEMA 14-50R 50A

NEMA L5-30R 120VAC | GX-0005 option CS6369A 50A twist lock receptacle

| *MODEL NO.* | GEN-13000-1MSE | GEN-14000-1MHE |
|---|---|---|
| *MAX. AC OUTPUT* | 13000 watts | 14000 watts |
| *RATED AC OUTPUT* | 11500 watts | 12000 watts |
| *DISPLACEMENT/ENGINE* | 650cc Subaru OHV with electric start - battery included | 688cc Honda OHV with electric start - battery included |
| *FREQUENCY/VOLTAGE* | Brushless 120V/240V, 60Hz | Brushless 120V/240V, 60Hz |
| *MAX. AMPS (120V/240V)* | 108.3/54.2 | 116.7/58.3 |
| *CONT. AMPS (120V/240V)* | 95.8/47.9 | 100.0/50.0 |
| *RECEPTACLES* | (2) 120V, 20A GFCI duplex / (1) 120V, 30A twist lock<br>(1) 120V/240V, 30A twist lock / (1) 120V/240V, 50A | (2) 120V, 20A GFCI duplex / (1) 120V, 30A twist lock<br>(1) 120V/240V, 30A twist lock / (1) 120V/240V, 50A |
| *CIRCUIT BREAKERS* | (2) 20A toggle circuit breaker, single pole / (1) 30A toggle circuit breaker, single pole / (1) 30A toggle circuit breaker, double pole / (1) 50A toggle circuit breaker, double pole | (2) 20A toggle circuit breaker, single pole / (1) 30A toggle circuit breaker, single pole / (1) 30A toggle circuit breaker, double pole / (1) 50A toggle circuit breaker, double pole |
| *RATED SPEED* | 3600 RPM | 3600 RPM |
| *DECIBEL RATING* | 77.5 | 77.5 |
| *FUEL CAPACITY* | 13.2 gallons | 13.2 gallons |
| *RUN TIME (AT FULL LOAD)* | 8.8 hours | 8.0 hours |
| *IDLE CONTROL* | Yes | Yes |
| *DIMENSIONS (LxWxH)* | 31.5x30.5x37.5in. | 31.5x30.5x37.5in. |
| *SHIP WT.* | 573 lb. | 568 lb. |
| *NET WT.* | 513 lb. | 508 lb. |

*Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.*

### Accessories & Options:

| *PART NUMBER* | *DESCRIPTION* | *FITS MODELS* |
|---|---|---|
| 32-0915 | RV generator adapter | All models |
| AW-6000-1002 | Equipment cover | All models |

| *PART NUMBER* | *DESCRIPTION* | *FITS MODELS* |
|---|---|---|
| GX-0003 | Skid feet | All models |
| GX-0005 | 50-amp twist lock receptacle | All models |