

3000, 4000 & 5000-Watt Gasoline

This portable generator provides dependable power for homeowners seeking a reliable electrical backup and is powerful enough for most industrial and contractor needs.

All Models Feature:

Engine

- Low-oil shutdown engine

Alternator

- Total harmonic distortion (THD) less than 5%
- 100% copper windings

Frame

- Heavy-duty wraparound frame with 1-inch powder coated steel tubing
- Low profile, compact design
- Angled isolator design features four neoprene isolators

Components

- Large low-tone mufflers to reduce noise to lowest level possible
- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Fuel shut-off valve
- Heavy-duty industrial air cleaners hold up under extreme conditions

Miscellaneous

- USDA/USFS-approved spark arrestors
- Circuit breaker protected

GEN-3000-1MH0 Model Additional Features:

Alternator

- Brushless 120V alternator

Components

- Large fuel tank capacity for extended run time



GEN-5000-OMS0 shown with optional wheel kit (AW-5740-0009)

GEN-4000 & GEN-5000 Model Additional Features:

Alternator

- Brushless 120V/240V alternator

Components

- Easy-to-read fuel gauge
- Full power switch
- Fuel tanks are powder coated outside, zinc-plated inside to prevent rusting

Warranties on All Models


| | | | |
|-----------------------|-----------------------|------------------------|------------------------|
| 2 YEAR LIMITED | 3 YEAR LIMITED | 3 YEAR LIMITED | 5 YEAR LIMITED |
| ALTERNATOR WARRANTY | HONDA ENGINE WARRANTY | KOHLER ENGINE WARRANTY | SUBARU ENGINE WARRANTY |

| MODEL NUMBER | GEN-3000-1MH0 | GEN-4000-OMH0 / GEN-4000-OMS0 | GEN-5000-OMK0 / GEN-5000-OMS0 |
|-------------------------|-----------------------|---|---|
| MAX. AC OUTPUT | 3000 watts | 4000 watts | 5000 watts |
| RATED AC OUTPUT | 2450 watts | 3500 watts | 4400 watts |
| DISPLACEMENT/ENGINE | 163cc Honda OHV | 242cc Honda OHV / 211cc Subaru OHC | 277cc Kohler OHV / 287cc Subaru OHC |
| FREQUENCY/VOLTAGE | 60Hz/120V | 60Hz/120V/240V | 60Hz/120V/240V |
| MAX. AMPS (120V/240V) | 25.0 | 33.3/16.7 | 41.7/20.8 |
| CONT. AMPS (120V/240V) | 20.4 | 29.2/14.6 | 36.7/18.3 |
| RECEPTACLES | 120V, 20A GFCI duplex | (2) 120V, 20A GFCI duplex 120V/240V, 20A twist lock 120V, 30A twist lock | (2) 120V, 20A GFCI duplex 120V/240V, 20A twist lock 120V, 30A twist lock |
| MAIN CIRCUIT BREAKERS | 20A push-button | (2) 20A toggle circuit breaker, single pole 20A toggle circuit breaker, double pole 30A toggle circuit breaker, single pole | (2) 20A toggle circuit breaker, single pole 20A toggle circuit breaker, double pole 30A toggle circuit breaker, single pole |
| RATED SPEED | 3600 RPM | 3600 RPM | 3600 RPM |
| DECIBEL RATING | 74.8 | 75.7 / 74.0 | 73.8 |
| FUEL CAPACITY | 2.6 gallons | 5.7 gallons | 5.7 gallons |
| RUN TIME (AT FULL LOAD) | 7.4 hours | 9.3 hours | 6.8 hours |
| DIMENSIONS (LxWxH) | 25in.x18in.x18in. | 29in.x19.75in.x22.5in. | 29in.x19.75in.x22.5in. |
| SHIP WT. | 146 lb. | 164 / 168 lb. | 198 lb. |
| NET WT. | 130 lb. | 142 / 146 lb. | 176 lb. |

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.

ACCESSORIES & OPTIONS

| PART NUMBER | DESCRIPTION | FITS MODELS |
|--------------|---|-------------------------|
| 32-0915 | RV generator adapter - 30A/125V female/male; use to connect RV cordsets to 30A generators | 4000 & 5000-watt models |
| AW-5090-0003 | Lifting hook - For easier portability, folds down and out of the way when not in use | 4000 & 5000-watt models |
| AW-5740-0009 | Wheel kit - For easier portability, pneumatic tires and rubber gripped handles | 4000 & 5000-watt models |
| AW-6000-1002 | Equipment cover - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover | All models |
| GX-0004 | Hour meter - Displays number of hours the unit has been in operation | 4000 & 5000-watt models |



GFCI 5-20R



NEMA L14-20R
125/250V



NEMA L5-30R
125 VAC



CSA
CERTIFIED