

3200, 5500, 6000 & 7500-Watt Gasoline

ChoreMaster® Series


With commitment to quality and performance, Mi-T-M ChoreMaster® generators offer great power in a compact package. They provide maximum output under any given situation and are durable and reliable featuring the Mi-T-M OHV engine.



GEN-3200-OMMO



GEN-6000-SMHO



GFCI 5-20R



NEMA L14-20R
125/250V



NEMA L14-30R
125/250V



CSA
CERTIFIED

All Models Feature Engine

- Mi-T-M OHV engine with low-oil shutdown
- Recoil starting system

Alternator

- 100% copper windings

Frame

- Low profile, compact design
- Heavy-duty wraparound frame with 1-inch powder coated steel tubing

Components

- Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles
- Large low-tone mufflers
- Fuel shut-off valve
- Heavy-duty industrial air cleaners hold up under extreme conditions

Miscellaneous

- USDA/USFS-approved spark arrestors
- Circuit breaker protected

Warranties

1 YEAR LIMITED
Mi-T-M ENGINE WARRANTY

2 YEAR LIMITED
ALTERNATOR WARRANTY

3 YEAR LIMITED
HONDA ENGINE WARRANTY

GEN-3200-OMMO Model Additional Features

Alternator

- Brushless 120V alternator
- Total harmonic distortion (THD) less than 6%

GEN-5500-OMMO, GEN-6000-SMHO & GEN-7500-OMMO Model

Additional Features

Alternator

- Brushless 120V/240V alternator
- Total harmonic distortion (THD) less than 5%

Components

- Fuel gauge
- Fuel tanks are powder coated outside, zinc-plated inside to prevent rusting

Models are compliant in 49 states. Cannot be sold in California.

Model Number	GEN-3200-OMMO	GEN-5500-OMMO	GEN-6000-SMHO	GEN-7500-OMMO
Max. AC Output	3200 watts	5500 watts	6000 watts	7500 watts
Rated AC Output	2600 watts	4800 watts	5500 watts	6500 watts
Displacement/Engine	208cc Mi-T-M OHV	291cc Mi-T-M OHV	337cc Honda OHV	414cc Mi-T-M OHV
Frequency/Voltage	60Hz/120V	60Hz/120V/240V	60Hz/120V/240V	60Hz/120V/240V
Max. Amps (120V/240V)	26.7	45.8/22.9	50.0/25.0	62.5/31.25
Cont. Amps (120V/240V)	21.7	40.0/20.0	45.8/22.9	54.2/27.1
Receptacles	120V, 20A GFCI duplex	(2) 120V, 20A GFCI duplex 120V/240V, 20A twist lock	(2) 120V, 20A GFCI duplex 120V/240V, 20A twist lock	(2) 120V, 20A GFCI duplex 120V/240V, 30A twist lock
Main Circuit Breakers	20A push-button	(2) 20A toggle circuit breaker, single pole 20A toggle circuit breaker, double pole	(2) 20A toggle circuit breaker, single pole 20A toggle circuit breaker, double pole	(2) 20A toggle circuit breaker, single pole 30A toggle circuit breaker, double pole
Rated Speed	3600 RPM	3600 RPM	3600 RPM	3600 RPM
Fuel Capacity	2.7 gallons	5.7 gallons	7.3 gallons	7.3 gallons
Run Time (at full load)	5.9 hours	6.8 hours	6.9 hours	6.9 hours
Dimensions (LxWxH)	25in.x18in.x18in.	27.5in.x19.75in.x22.5in.	28in.x24.5in.x22.25in.	28in.x24.5in.x22.25in.
Ship Wt.	140 lbs.	186 lbs.	228 lbs.	228 lbs.
Net Wt.	117 lbs.	163 lbs.	203 lbs.	203 lbs.

ACCESSORIES

Part Number	Description	Fits Models
AW-5090-0001	Lifting hook - For easier portability, folds down and out of the way when not in use	GEN-5500-OMMO
AW-5090-0002	Lifting hook - For easier portability, folds down and out of the way when not in use	GEN-6000 & GEN-7500
AW-5740-0012	Wheel kit - For easier portability, pneumatic tires with tubes, rubber gripped handles	GEN-5500-OMMO
AW-5740-0013	Wheel kit - For easier portability, pneumatic tires with tubes, rubber gripped handles	GEN-6000 & GEN-7500