Portable Generators

6000, 7500 & 8000-Watt

Gasoline

Designed for the serious contractor with multiple voltage applications and power needs. This unit features a wraparound frame making it a must for every jobsite.

To see more online, scan here or go to www.mitm.com:

GEN-8000-0MSE

Alternator
- *Total harmonic distortion (THD) less than 5%*
- *100% copper windings*

Frame
- *Heavy-duty wraparound frame with 1-inch steel tubing*
- *Angled isolator design features neoprene isolators*

Components
- *Easy-access and protected control panel with magnetic circuit breakers and GFCI-protected receptacles*
- *Large low-tone mufflers*
- *Fuel shut-off valve*
- *Easy-to-read fuel gauge*
- *Voltmeter/hour meter*
- *Heavy-duty industrial air cleaner*

Miscellaneous
- *USDA/USFS-approved spark arrestors*

Limited Warranties:

2 Year Alternator
3 Year Kohler Engine
3 Year Honda Engine
5 Year Subaru Engine

CSA CERTIFIED



GFCI 5-20R All Models | NEMA L14-20R 120V/240V GEN-6000 Models | NEMA L14-30R 120V/240V GEN-7500 & 8000 Models | NEMA L5-30R 120VAC All Models

MODEL NO.	GEN-6000-0MH0* / GEN-6000-0MK0 / GEN-6000-0MS0*	GEN-7500-0MH0*	GEN-8000-0MK0* / GEN-8000-0MS0*
MAX. AC OUTPUT	6000 watts	7500 watts	8000 watts
RATED AC OUTPUT	5000 watts	6500 watts	6900 watts
DISPLACEMENT/ENGINE	389cc Honda OHV / 429cc Kohler OHV / 404cc Subaru OHC	389cc Honda OHV	429cc Kohler OHV / 404cc Subaru OHC
ALTERNATOR	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz	Brushless 120V/240V, 60Hz
MAX. AMPS (120V/240V)	50.0/25.0	62.5/31.25	66.7/33.3
CONT. AMPS (120V/240V)	41.7/20.8	54.2/27.1	57.5/28.75
RECEPTACLES	(2) 120V, 20A GFCI duplex (1) 120V/240V, 20A twist lock (1) 120V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock	(2) 120V, 20A GFCI duplex (1) 120V, 30A twist lock (1) 120V/240V, 30A twist lock
CIRCUIT BREAKERS	(1) Main circuit breaker (2) 20A toggle circuit breaker, single pole (1) 20A toggle circuit breaker, double pole (1) 30A toggle circuit breaker, single pole	(2) 20A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole	(2) 20A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, single pole (1) 30A toggle circuit breaker, double pole
RATED SPEED	3600 RPM	3600 RPM	3600 RPM
DECIBEL RATING	77.1 / 77.1 / 77.4	80.0	78.2
FUEL CAPACITY	7.3 gallons	7.3 gallons	7.3 gallons
RUN TIME (AT FULL LOAD)	8.0 hours / 8.0 hours / 7.9 hours	6.9 hours	6.9 hours
IDLE CONTROL	Yes	Yes	Yes
DIMENSIONS (LxWxH)	29x24.4x22.5in.	29x24.4x22.5in.	29x24.4x22.5in.
SHIP WT.	232 lb.	255 lb.	245 lb.
NET WT.	210 lb.	233 lb.	233 lb.

Noise level tested at seven meters (75% load). Rating represents minimum noise level rating.
**Available with electric start - battery included.*

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
32-0915	RV generator adapter	All models
AW-5090-0004	Lifting hook	All models

PART NUMBER	DESCRIPTION	FITS MODELS
AW-5740-0010	Wheel kit	All models
AW-6000-1002	Equipment cover	All models

Mi-T-M Corporation · 50 Mi-T-M Drive · Peosta, IA 52068 · 800-553-9053 · 563-556-1235 fax · corp@mitm.com · www.mitm.com