

ChemGrout®

CG-570 Thick-Mix Series

Simple, powerful and built to last, the Thick-Mix Series is ideal for mixing, pumping and spraying a wide range of materials, such as repair mortars, stucco, plasters, fireproofing and finish coats.

CG-570/3C6/H
Hydraulic Powered

CG-PU15/EH/AC
Electric/Hydraulic
Power Pack



Powerful size 6 progressive cavity pump provides a smooth, easy to control delivery of both thick and thin materials.

A 45-gallon (170 liter) mixing tank, large holding hopper and centrally located controls, ensure non-stop production with a single operator.

High-strength aluminum alloy pump features easy access for both cleaning and maintenance.

Power options include air, hydraulic, gas/hydraulic, electric/hydraulic, and diesel/hydraulic.

CG-575/3C6/GH
Gas/Hydraulic Powered



ChemGrout®

Widest Selection of Grouting Equipment in the World

CG-570 Thick-Mix Series - Versatile, Durable and Reliable

With its rugged steel construction, the versatile CG-570 Thick-Mix Series mixes and pumps a wide range of materials from thick mortars to thin finishing coats. Optional built-in air compressors (12 cfm for thin and 15 cfm for thick materials) allow even more flexibility for a host of spray applications. Easy to operate and inexpensive to maintain, these time tested grout plants provide quick set-up, smooth pumping, simple clean-up and long term durability.

The dependable Thick-Mix Series is complete and ready for jobsite operation. The heavy-duty 45-gallon mix tank is equipped with bag breaker, baffles and a variable speed high-efficiency paddle mixer that provides high shearing action for thorough and complete particle wetting. The tank outlet valve is a large slide gate that allows the thickest materials to fall easily into the pump's sloped holding hopper. The CG-570's 15-gallon hopper is covered with a removable metal screen, preventing debris or dry material clumps from falling into the pump. Additional mixing is provided

through the use of an auger inside the suction housing, which then feeds the unit's durable 3C6 pump. This efficient method of using a holding hopper allows one batch to be pumped while another is mixed, ensuring a non-stop output of material.

The Thick-Mix Series utilizes a size 6 open throat progressive cavity pump, featuring a non-pulsating positive displacement rotor-stator that provides a constant discharge of materials. This steady material flow is essential for many spray and injection applications. Outputs range up to a maximum of 8 gpm (30 lpm), with pressures of 261 psi (18 bar). The pump's new high-strength aluminum alloy construction offers durability and a weight reduction of 33% over that of similar pumps. A hinged cleanout port has also been added to the suction housing for quick access and easy clean up. Both mixer and pump controls are centrally located and are variable speed. Widely regarded as the industry standard, the Thick-Mix Series is easy-to-use, complete, and ready for the toughest jobsite conditions.



Large slide gate allows an easy transfer of thick materials.




Hinged cleanout port provides quick access and easy clean up.

Specifications

| CG-570/3C6 Skid - Power | Required | Weight | Size |
|------------------------------|------------------|---------|-----------------|
| Air | 250 CFM, 100 PSI | 750 Lbs | 74" x 31" x 53" |
| Hydraulic | 15 GPM, 2000 PSI | 750 Lbs | 74" X 31" x 58" |
| Hydraulic Power Packs | Power | Weight | Size |
| Elec./Hyd. w/air compressor | * 3 Phase | 865 Lbs | 57" x 29" x 44" |
| Gas/Hyd. w/air compressor | Self-Contained | 755 Lbs | 48" x 40" x 36" |
| Diesel/Hyd. w/air compressor | Self-Contained | 795 Lbs | 54" x 40" x 39" |

| CG-575/3C6 Trailer - Power | Required | Weight | Size |
|------------------------------|----------------|----------|------------------|
| Gas./Hydraulic | Self-Contained | 1450 Lbs | 110" x 62" x 70" |
| Gas/Hyd. w/air compressor | Self-Contained | 1500 Lbs | 110" x 62" x 70" |
| Diesel/Hyd. w/air compressor | Self-Contained | 1625 Lbs | 110" x 62" x 70" |

ChemGrout's CG-PU20/DH Diesel/Hydraulic Power Pack



Separate power packs provide a clean, quiet and vibration free working environment.

*Several Voltages Available




Waterproofing



Fireproofing



Manhole Sealing



Concrete Restoration

Applications include:

Cement block filling, waterproofing, slabjacking, void filling, tie backs, anchoring rock bolts, undersealing, slab raising, underlayments, bonded overlay, bridge rehabilitation, dowel bars, and manhole sealing.

ChemGrout®

Widest Selection of Grouting Equipment in the World

ChemGrout, Inc., P.O. Box 1140, 805 E. 31st Street, LaGrange Park, IL 60526 USA • Phone: (708) 354-7112 • Fax: (708) 354-3881

Visit our web site: www.chemgrout.com • E-mail: info@chemgrout.com