

26" **OSCILLATING** Abrasive Cut-Off

Specifications

Wheel Capacity

26" diameter.

Arbor Shaft

1 inch.

Motor

Special hi-torque totally-enclosed fan-cooled 30 or 40 H.P. 3 phase. Oscillator 1/3 H.P. gear motor.

Starter

Magnetic with thermal overload all motors. 110 volt at controls.

Drive

Positive timing belt.

Spindle Bearings

Heavy-duty sealed ball bearings. Lubricated for life.

Capacity

6" dia. solids. Most 7" shapes. 12" channel with optional fixture.

Safety Guards

Cut-off wheel and belt guards exceed safety code requirements.

Vise

Sturdy work fence, screw clamp.

Air operation optional.

Stop

Adjustable down stop limits depth of chop stroke.

Exclusive Vibra-Action

OSCILLATION

For improved cutting, reduced burr and longer wheel life.

Options

Hydraulic Power Head

With hydraulic feed control valve for smooth, accurate cutting speed.

Electronic Wheel Wear

Compensator

(See page 16.)

Work Length Gage

Patented Dust Collector Fume

Exhauster (See page 17.)


"V" Block Air Vise

Mitering Work Fence

To cut miters 45° right or left of 90°.

Hood

Shipping Weight 1165 lbs., 10 wheels, 125 lbs.



Exclusive vibra-action oscillation moves the wheel back and forth while cut is being made. This reduces the area of contact between the wheel and material, resulting in improved quality of cut, less heat build up, less burr and increased wheel life.



Featured with optional hydraulic power head, and air operated "V" shaped chain holddown vise

Dry Cutting Speeds (average)		
Size	Material	Time
6"	Solid	115 sec.
8" x 8"	Angle	20 sec.
12"	Channel	40 sec.

COMPLETE with TEFC motor, magnetic starters OSCILLATION and vise (specify H.P., voltage/phase/hertz when ordering USE CHART AT RIGHT)	2602EF
COMPLETE as above with hydraulic powerhead	2622EF
COMPLETE as above with electronic wheel wear compensator	2642EF
COMPLETE with TEFC motor, magnetic starters OSCILLATION and mitering fence (specify H.P., voltage/phase/hertz when ordering USE CHART AT RIGHT)	2603EF
COMPLETE as above with hydraulic powerhead	2623EF
COMPLETE as above with electronic wheel wear compensator	2643EF
Air operated clamp for straight or miter fence	269480
Air operated "V" shaped chain holddown vise (see above)	269410
Dust collector fume exhauster (see page 17)	269201
Hood	269010
Adjustable outboard support (see pages 17)	269403
24" work length gage (not available with miter fence)	269402
Fixture for cutting up to 12" channel	269490

HORSEPOWER AND VOLTAGE CODES
FOR H.P. REPLACE "E" WITH
 7 = 30 HP 8 = 40 HP
FOR VOLTAGE REPLACE "F" WITH
 2 = 208/3/60 3 = 230/3/60
 4 = 380/3/50 5 = 440/3/60
 7 = 575/3/60 CALL FOR OTHERS

Prices and design subject to change without notice.