

Single Stage Electric

Portability is key at every jobsite. The 8-gallon air compressor features an industrial electric motor, auto start/stop and flat-free tires that are perfect for transporting from one job to the next.

To see more online, scan here
or go to www.mitm.com:



Compressor Pump

- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

Motor

- Auto start/stop - continuous run optional
- Thermal overload motor protection

Frame

- Powder coated 8-gallon twin tank receivers
- 3/16-inch base plate to reduce vibration
- 16-gauge powder coated two-piece belt guard
- Flat-free tires

Components

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 10-inch fly wheel
- Industrial-grade pressure switch



AM1-PE02-08M

Limited Warranties:

1 Year
Electric Motor

2 Year
Pump Exchange

See page 60 for information



CSA CERTIFIED



NEMA 5-15P,
15-amp plug



NEMA 5-20P,
20-amp plug

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	COMPRESSOR	TANK SIZE	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM1-PE15-08M	7.3 @ 90	1.5 HP, 120V, 13.2A	Single stage, cast iron	8-gallon	NEMA 5-15P	44.5x18.5x25in.	190 lb.	170 lb.
AM1-PE02-08M	9.2 @ 90	2.0 HP, 120V, 18.8A	Single stage, cast iron	8-gallon	NEMA 5-20P	44.5x18.5x25in.	190 lb.	170 lb.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
AW-6000-1002	Equipment cover	All models	AX-0003	Manual drain/regulator/metal bowl	All models
AX-0002	Auto drain/regulator/plastic bowl	All models	AX-0005	Dual control - continuous run & auto start/stop	All models