


Cold Water Electric Belt Drive

CW Premium Series

The electric version of the CW Series is perfect for heavily-soiled commercial and industrial equipment that requires indoor cleaning. Much quieter than the gas models, there is no need to worry about proper ventilation because of exhaust fumes.



CW-3004-4ME3



NEMA L15-30P,
30-amp plug

NEMA 15-50P,
50-amp plug

NEMA 6-50P,
50-amp plug



External bypass system allows more water into the system to protect from heat build-up

Pump

- Belt drive triplex piston General pump with ceramic plungers
- Stainless-steel and brass unloader
- Forged brass manifold
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

Motor

- Totally enclosed fan-cooled electric motor with thermal overload protection
- 10-foot power cord

Frame

- Powder coated steel tube handles and base plate
- Totally enclosed powder coated steel belt guard
- Convenient gun/wand holder and hose wrap
- Solid steel threaded axle
- Pneumatic tires and dual rubber isolators

Component

- Heavy-duty dual cogged belt drive system for increased belt life

Units Include:

- Quick connect nozzles (0°, 15°, 25° and 40°)
- 50-foot x 3/8-inch non-marking hose with quick connects, swivel and bend restrictors
- Professional-grade insulated trigger gun with safety lock-off
- 36-inch lance with rubber grip (48-inch on 4000 & 5000-PSI models)

Warranties



MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
CW-2405-4ME1	2400	4.6	7.5 HP, 230V, 1Ø, 35.7A	NEMA 6-50P	46in.x28in.x30in.	345 lb.	333 lb.
CW-2405-4ME3*	2400	4.6	8.0 HP, 230V, 3Ø, 24.7A or 8.0 HP, 460V, 3Ø, 11.5A	NEMA L15-30P	46in.x28in.x30in.	255 lb.	243 lb.
CW-3004-4ME1	3000	3.5	7.5 HP, 230V, 1Ø, 35.0A	NEMA 6-50P	46in.x28in.x30in.	350 lb.	338 lb.
CW-3004-4ME3*	3000	3.5	8.0 HP, 230V, 3Ø, 23.0A or 8.0 HP, 460V, 3Ø, 11.5A	NEMA L15-30P	46in.x28in.x30in.	330 lb.	318 lb.
CW-3005-OME1	3000	4.8	10.0 HP, 230V, 1Ø, 37.5A	NEMA 6-50P	45.5in.x32.5in.x30in.	470 lb.	396 lb.
CW-3005-OME3*	3000	4.8	10.0 HP, 230V, 3Ø, 25.6A or 10.0 HP, 460V, 3Ø, 12.8A	NEMA 15-50P	45.5in.x32.5in.x30in.	450 lb.	376 lb.
CW-4004-OME3*	4000	3.9	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	NEMA 15-50P	45.5in.x32.5in.x30in.	505 lb.	431 lb.
CW-5004-OME3*	5000	4.0	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	NEMA 15-50P	45.5in.x32.5in.x30in.	505 lb.	431 lb.

*460V motors available as options.

ACCESSORIES & OPTIONS

PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injection - High pressure water mixes with detergent to clean even the heaviest build-up	All models
AW-8400-0021	Low pressure detergent injection - Allows the user to apply the recommended detergents	All models
CX-0003	460V, 3-phase models - For when you have 460V of power available	CW-2405-4ME3 & CW-3004-4ME3
CX-0005	Insulated dual lance - Has both a high and low pressure tip that allows you to switch to the low pressure chemical injector without having to change tips	All models
CX-0057	460V, 3-phase models - For when you have 460V of power available	CW-4004-OME3 & CW-5004-OME3
CX-0062	460V, 3-phase models - For when you have 460V of power available	CW-3005-OME3