

Hot Water Natural Gas/LP Belt Drive

HG Series

The stationary HG Series is a perfect choice for wash bays that require a steady fuel source. Available in either natural gas or LP, these units feature an electronic ignition with an intermittent pilot.

Limited Warranties:

- 1 Year** Electric Motor
- 7 Year** Pump
- 3 Year** Coil



Pump

- ✓ Thermal relief valve
- ✓ Adjustable high pressure detergent injector

Motor

- ✓ Open drip-proof motor with thermal overload protection

Frame

- ✓ Powder coated steel side panels and frame

Components

- ✓ Natural gas or LP gas-fired (vapor only) natural draft with aspirating-type burner, 10-inch stack
- ✓ 24-volt control system
- ✓ 1/2-inch schedule 80-coil heat exchanger
- ✓ Electronic ignition with an intermittent pilot

Unit Includes:

- ✓ 50-foot x 3/4-inch steel wire-braided pressure hose with quick connects
- ✓ Insulated trigger gun with safety lock-off
- ✓ Adjustable pressure insulated dual lance

Miscellaneous

- ✓ Maximum outlet temperature is 200°F (250°F/121°C outlet temperature with steam option)



HG-3004-3460

To see more online, scan here or go to www.mitm.com:



Professional Installation Required

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	Mi-T-M NO.	UNLOADER	BTU PER HR. NATURAL GAS	BTU PER HR. LP GAS	DRAFT DIVERTER	NOZZLES	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
HG-3004-1208	3000	3.9	8.0 HP, 208V, 1Ø, 40.5A	General	3-0202	Factory preset	338,000	326,000	21in.	0°, 15°, 25° & 40°	56.5x29x49.75in.	878 lb.	758 lb.
HG-3004-3208	3000	3.9	8.0 HP, 208V, 3Ø, 23.0A	General	3-0202	Factory preset	338,000	326,000	21in.	0°, 15°, 25° & 40°	56.5x29x49.75in.	878 lb.	758 lb.
HG-3004-1230	3000	3.9	8.0 HP, 230V, 1Ø, 37.0A	General	3-0202	Factory preset	338,000	326,000	21in.	0°, 15°, 25° & 40°	56.5x29x49.75in.	878 lb.	758 lb.
HG-3004-3230	3000	3.9	8.0 HP, 230V, 3Ø, 20.0A	General	3-0202	Factory preset	338,000	326,000	21in.	0°, 15°, 25° & 40°	56.5x29x49.75in.	878 lb.	758 lb.
HG-3004-3460	3000	3.9	8.0 HP, 460V, 3Ø, 10.0A	General	3-0202	Factory preset	338,000	326,000	21in.	0°, 15°, 25° & 40°	56.5x29x49.75in.	878 lb.	758 lb.

Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
HX-0104	K7 unloader, flow activated (auto start/stop N/A)	All models	HX-0110	Additional remotes (up to 3)	All models
HX-0105	Liquid propane (vapor only)	All models	HX-0111	Auto start/stop	All models
HX-0106	Hour meter	All models	HX-0121	250°F steam upgrade	All models
HX-0107	Time delay shutdown	All models	HX-0124	Auto start/stop and first remote option	All models
HX-0108	(1) remote station (auto start/stop N/A)	All models	<i>Note: You cannot order HX-0107 and HX-0108 together, you will need to order HX-0109 instead. HX-0107 and HX-0108 can be ordered separately.</i>		
HX-0109	Time delay shutdown and first remote box	All models			