

Cold Water Electric Direct Drive

JP Series


Designed for medium-duty, commercial use, the portable electric JP Series features quiet operation with no exhaust which is ideal for indoor applications where exhaust fumes are prohibited.




Limited Warranties:

1 Year Electric Motor


7 Year Pump




UL
USA & Canada:
JP-1002 &
JP-1502 models




CSA
USA Only:
JP-2003, JP-2503 &
JP-3004 models




NEMA 5-15P,
15-amp plug




NEMA 5-20P,
20-amp plug




NEMA L15-20P,
20-amp plug




NEMA 6-20P,
20-amp plug



NEMA L15-30P,
30-amp plug



NEMA 6-30P,
30-amp plug



NEMA 6-50P,
50-amp plug



JP-3004-OME3

Pump

- ✓ Forged brass manifold
- ✓ Thermal and safety relief valves
- ✓ Adjustable low pressure detergent injector

Motor

- ✓ Totally enclosed fan-cooled electric motor
- ✓ 35-foot power cord (GFCI on 1.5 to 6.0-HP single-phase models) (10-foot power cord on 8.0-HP models)

Frame

- ✓ Powder coated steel tube handles and base plate

Unit Includes:

- ✓ 50-foot x 3/8-inch non-marking hose with quick connects (25-foot on JP-1002, JP-1502 & JP-2003 models)
- ✓ Insulated trigger gun with safety lock-off

To see more online, scan here or go to www.mitm.com:



MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	MI-T-M NO.	UNLOADER	PLUG TYPE	NOZZLES	LANCE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
JP-1002-3ME1	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	AR	3-0362	Adjustable pressure	NEMA 5-15P	Variable high/low pressure	36in.	37x21x24.5in.	120 lb.	90 lb.
JP-1002-2ME1*	1000	2.0	1.5 HP, 120V, 1Ø, 15.0A	General	3-0278	Adjustable pressure	NEMA 5-15P	Variable high/low pressure	36in.	37x21x24.5in.	120 lb.	90 lb.
JP-1502-3ME1	1500	2.0	2.0 HP, 120V, 1Ø, 17.0A	AR	3-0362	Adjustable pressure	NEMA 5-20P	Variable high/low pressure	36in.	37x21x24.5in.	120 lb.	90 lb.
JP-1502-2ME1*	1500	2.0	2.0 HP, 120V, 1Ø, 17.0A	General	3-0278	Adjustable pressure	NEMA 5-20P	Variable high/low pressure	36in.	37x21x24.5in.	120 lb.	90 lb.
JP-2003-3ME1	2000	2.6	4.0 HP, 230V, 1Ø, 16.0A	AR	3-0364	Adjustable pressure	NEMA 6-20P	Variable high/low pressure	36in.	37x21x24.5in.	162 lb.	112 lb.
JP-2503-1ME1	2500	3.2	6.0 HP, 230V, 1Ø, 24.1A	AR	3-0307	Adjustable pressure	NEMA 6-30P	0°, 15° & 25°	36in.	44x26x27in.	275 lb.	225 lb.
JP-2503-OME3	2500	3.2	6.0 HP, 230V, 3Ø, 15.0A or 6.0 HP, 460V, 3Ø, 7.5A	AR	3-0307	Adjustable pressure	NEMA L15-20P	0°, 15° & 25°	36in.	44x26x27in.	275 lb.	225 lb.
JP-3004-1ME1	3000	3.9	8.0 HP, 230V, 1Ø, 34.5A	AR	3-0207	Adjustable pressure	NEMA 6-50P	0°, 15° & 25°	36in.	44x26x27in.	275 lb.	225 lb.
JP-3004-OME3	3000	3.9	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	AR	3-0207	Adjustable pressure	NEMA L15-30P	0°, 15° & 25°	36in.	44x26x27in.	275 lb.	225 lb.

*Pump accepts incoming water up to 175°F.

Accessories & Options:

PART NUMBER	DESCRIPTION	FITS MODELS	PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector	All models	CX-0066	460V on 6.0-HP, 3-phase model	JP-2503-OME3
CX-0005	Insulated dual lance	All models	CX-0067	460V on 8.0-HP, 3-phase model	JP-3004-OME3
CX-0030	50-foot high pressure hose	1000 to 2000-PSI models			